

Product Information

Sangoma SBC Appliance

Fully integrated Industrial grade telco appliance running a customized OS, Sangoma SBC Application and Media interfaces configured and installed by Sangoma. Sangoma SBC Appliance provides a full-featured, carrier-class SBC deployment while leveraging the flexibility and cost effectiveness of standard computing platforms

Hardware Specifications

Carrier Hardware Specification	Enterprise Hardware Specification
Industrial grade telecom appliance	Industrial grade telecom appliance
Size: 1U and 2U – 19" Rack mount	Size: 1U and 2U – 19" Rack mount
Min Capacity: 250 Sessions/Calls (1U)	Min Capacity: 25 Sessions/Calls (1U)
Max Capacity: 4000 Sessions/Calls (1U/2U)	Max Capacity: 250 Sessions/Calls (1U)
Power: AC, DC, Redundant AC/DC	Power: AC Only
AC Power Supply (Redundant)	
110V/220V	110V/220V
DC Power Supply (Redundant) The Input Current for -48VDC, is 12.0A (RMS). With Inrush Current of 20.0A MAX.	
Depth: 20"	Depth: 8"
Weight: 36lb	Weight: 20lb
2 Gigabit Network Interfaces	2 Gigabit Network Interfaces
1 or 2 High Density DSP Interfaces	1 DSP Interface