

# Call Routing Examples

## Ignore Display Updates

Condition

Description: [ ] Rank: 10

Matching: All Stop Policy: Continue

Condition: Standard Information Name: Destination Address Expression: (.\*)

Condition: ( Please Select One )

Condition: ( Please Select One )

Condition: ( Please Select One )

Condition: ( Please Select One )

Actions to perform if condition matches

Action: Export Variable Name: ignore\_display\_updates Value: true

Action: Bridge to Trunk Trunk: to\_ITSP Destination: \$1

Action: ( Please Select One )

Action: ( Please Select One )

Action: ( Please Select One )

Actions to perform if condition doesn't match

Action: ( Please Select One )

Action: ( Please Select One )

## Use P-Asserted-Identity

Condition

Description: [ ] Rank: 10

Matching: All Stop Policy: Continue

Condition: Standard Information Name: Destination Address Expression: (.\*)

Condition: ( Please Select One )

Condition: ( Please Select One )

Condition: ( Please Select One )

Condition: ( Please Select One )

Actions to perform if condition matches

Action: Set Variable Name: sip\_h\_Privacy Value: id

Action: Bridge to Trunk Trunk: to\_ITSP Destination: \$1

Action: ( Please Select One )

Action: ( Please Select One )

Action: ( Please Select One )

Actions to perform if condition doesn't match

Action: ( Please Select One )

Action: ( Please Select One )

Action: ( Please Select One )

Action: ( Please Select One )

Action: ( Please Select One )

Save Cancel

## Use P-Preferred-Identify

Condition ( Please Select One )					
Actions to perform if condition matches					
Action	Export Variable	Name	forward_talk_and_hold_notifications	Value	true
Action	Export Variable	Name	enable-100rel	Value	true
Action	Export Variable	Name	sip_cid_type	Value	pid
Action	Export Variable	Name	origination_privacy	Value	hide_name
Action	Bridge to Trunk	Trunk	ITSP	Destination	S1

## Rate Limit Inbound calls from any calling party, per calling party

useful to prevent malicious dialers from repeated call attempts

The below screenshot is rate limiting a specific source for more than 1 call attempt with 8 seconds.

(alter as needed)

If the rate limit is reached/triggered, a 404 response will occur

**Basic Call Routing - To\_ITSP**

Description: to\_PBX  
Trace Call: Disable  
Default Response: 404

[Edit](#) [Cancel](#)

**Rule**

Showing 1 to 1 of 1 entries

#	Description	
10	IF MATCH Condition(All,Standard Information[Destination Address] = (.*)) THEN Custom[limit]=hash \${sip_network_ip} \${sip_from_user} 1/8"> Bridge to Trunk[to_PBX]=\$1 AND Continue	<a href="#">Edit</a> <a href="#">Delete</a>

[Add](#)